

KDC400 Barcode/MSR SLED for Smartphone

A New Wave in Auto-ID

The KDC400 enables diverse mobile Auto-Identification applications to collect barcode and MSR data with various Smartphones and Tablets.

KoamTac's innovative Bluetooth technology and user friendly design allows users to upgrade the smartphone periodically while keeping the KDC400 main system.

A Built-in 1200mAh rechargeable battery can be used as an external power source for smartphones.

An optional secondary Bluetooth port provides a seamless connectivity to other Bluetooth peripherals such as mobile printers.

KDC400 comes with FREE KTSync® keyboard wedging software and FREE SDK for Android, Blackberry, iOS (iPhone, iPod touch, iPad) and Windows.



ADVANCED FEATURES

- Custom case for smartphone
- Supports 1D and 2D barcodes
- Supports triple track and Japan double side track
- Class2 Bluetooth® with HID/SPP/ MFi(iPhone model only) Profiles
- Rechargeable Li-Ion Battery
- KTSync® with Keyboard Wedging features.



- Transportation
- Logistics
- Healthcare Services
- Field Services
- Distribution & Retail
- Property Management

KDC400 Specifications

Hardware Specifications

Physical Characteristics

Barcode Model (Basic)

- **Size** : 2.5" x 3.7" x 0.4~0.8"
(65mm x 95mm x 10~20mm)
- **Weight** : 3.3 oz. (94 grams)

Barcode/MSR Model (Basic)

- **Size** : 2.5" x 4.7" x 0.4~0.8"
(65mm x 121mm x 10~20mm)
- **Weight** : 4.0 oz. (115 grams)

Electrical Characteristics

Battery : Lithium-Ion (3.7V DC, 1200mAh)

Charging : Via USB connector

Typical Operating Current : 300mAh@3.3V

Scanning Performance

1D Laser : 100scans per second

2D Image : 752 x 480 CMOS sensor

User Environment

Drop Spec : 5 feet (1.5m)

Operating : 32°F (0°C) ~ 113°F (45°C)

Storage : -4°F (-20°C) ~ 113°F (45°C)

Humidity : 5% ~ 85% (noncondensing)

Interfaces

Bluetooth® V2.1+EDR, Class 2,
HID/SPP/MFi (Optional 2 ports)

Functionality

Memory Flash ROM : 256KB

Memory RAM : 64KB

Microprocessor : ARM7, 32 bits

Real-time Clock : Quartz RTC

Buzzer : 92dB

Button : 2 Scan, 1 Up, 1 Down

LED : 1 Tri-Color LED

Barcode Symbologies

1 Dimensional

EAN, UPC, Code 39, Code 93, Code 128, Codabar,
Interleaved 2 of 5, GS1-128, Code 3 of 5

2 Dimensional

All major 1D, 2D, Postal, OCR-A/B codes

MSR

- Comply with ISO7810/7811/7812 (Triple track) or JIS6220 (Japan double sided track)
- **Life** : Minimum 500,000 swipes
- **Swipe speed** : 3.9 to 50 inch/sec (10 to 150 cm/sec)

Wedging & Synchronization

- Keyboard wedge function
- Add-on prefixes and suffixes
- Barcode option selection

Regulatory Conformance

EMC - CE, FCC, KC, TELEC

Models

KDC410 – 1D Barcode Sled

KDC415 – 1D Barcode/MSR Sled

KDC420 – 2D Barcode Sled

KDC425 – 2D Barcode/MSR Sled

KDC430 – MSR Sled

KDC4xx – Custom model for a Smartphone

Package Contents

1 SLED with rechargeable battery,

1 SLED charging USB cable, 1 Smartphone charging
USB cable, 1 Hand strap, 1 Software CD

For more information, contact us at:

KoamTac, Inc.

116 Village Blvd. Suite 200
Princeton, NJ 08540, USA

Tel +1-609-734-4335

Fax +1-609-228-4373

E-mail info@koamtac.com

www.koamtac.com

