

LK-P20
Printer Innovation

LUKHAN



Innovation, High Quality Mobile Printer
The LKP Series



Mobile Printer

LK-P20

2 Inch Thermal Mobile Printer

- High speed (80mm/sec, MAX)
- USB, RS-232C, Bluetooth, Wi-Fi interface
- Support Magnetic Stripe Reader & Smart Card Reader
- Support text and graphic printing.
- Easier paper roll loading
- High resolution (203dpi)



LKP SERIES SPECIFICATION

LUKHAN

MODEL	LK-P20	
PRINT METHOD	Direct Thermal	
PRINTING SPEED	80mm/sec	
DOT DENSITY	203 DPI	
DOT PITCH	8dots/mm, 0.125 pitch	
EFFECTIVE PRINTING WIDTH	48mm, 384 Dots/Line	
PAPER	TYPE	Thermal paper
	WIDTH	58mm
	THICKNESS	65 μ m
	ROLL DIAMETER	Max. Φ 48mm
	ROLL CORE INNER DIAMETER	12.5mm \pm 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	1million pulse or more(12.5% print ratio)
CHARACTER SET	ALPHA NUMERIC CHARACTER	95
	EXTENDED GRAPHIC	128 x 18 page (1 space page)
	INTERNATIONAL CHARACTER	14
BARCODE	EAN-8, EAN-13, CODE39, ITF, UPC-A, CODABAR, CODE93, CODE128, PDF417(2D)	
EMULATION	ESC-POS	
DRIVER	Window CE 4.2&5.0, Window mobile 5.0	
SENSOR	Paper end sensor	
INTERFACE	STANDARD	Serial(RS-232C), USB 2.0
	OPTION	WiFi(802.11b/g), Bluetooth Class2
POWER	CHARGER	External Charger
	BATTERY	7.2V 2000mAH Li-ion
DIMENSION	Wmm x Dmm x Hmm	94 X 63 X 139
	W" x D" x H"	3.7 X 2.4 X 5.4
WEIGHT (With battery, Paperroll)	400g	
TEMPERATURE	OPERATING TEMPERATURE	5 ~ 40°C
	STORAGE TEMPERATURE	-20 ~ 60°C
HUMIDITY	OPERATING HUMIDITY	35 ~ 80%
	STORAGE HUMIDITY	10 ~ 90%

Specifications are subject to change without notice.

September 2007



LUKHAN

SEWOO TECH Co., Ltd.

Doosung Bd, 689-20, Kumjung-dong,
Kunpo-si, Kyunggi-do, Korea
Tel : 82-31-459-8200 Fax : 82-31-459-8880
E-mail : sales@miniprinter.com
www.miniprinter.com

www.miniprinter.com