



Symbol SE950/SE955

OEM scan engine



FEATURES

Large working range

Meets the needs of a wide range of applications for increased productivity

Small and light scan engine

Easily optimize product designs

100 scans per second

Optimized scanning speed delivers aggressive performance and accurate capture of all bar codes — even damaged and poor quality

Low power consumption

Increases battery life in portable terminals

Bright scan line and aim mode

Provides intuitive ease-of-use across the entire working range

Miniature scan engine sets new standard for performance, features and reliability

The Symbol SE950/SE955 miniature scan engine sets a new benchmark, offering best-in-class quality, reliability, durability and scanning performance. Scanning across the wide working range is easy, intuitive and rapid, regardless of environment. The durable engine design enables you to deliver products that perform reliably day in and day out, increasing productivity and reducing total cost of ownership. Regardless of whether you are designing handheld computers, medical instruments, diagnostic equipment, lottery terminals, robotics and more, these extremely small scan engines deliver next-generation performance with an ease of integration that enables rapid cost-effective product development — a true competitive advantage.

Durability for all day every day use

The Symbol SE950/SE955 offers superior reliability you can count on, regardless of whether you are incorporating the Symbol SE950/SE955 into mobile computers or laboratory analyzers. The patented Liquid Polymer Scan Technology is frictionless and will not wear out. Designed for durability, the elimination of fragile silicon mirrors combined with the die cast chassis enables the Symbol SE950/SE955 to handle drop shocks up to 2000Gs. You enjoy maximum uptime — and a lower total cost of ownership.

Increased productivity

The highly advanced retro-collective optical design provides a superior working range, regardless of lighting or bar code symbology. Scanning speed is optimized to provide aggressive read times, and the programmable scan line is easily adjusted, providing the flexibility to use a single scan engine for a wide variety of uses. The result is the rapid and accurate scanning needed to improve worker productivity.

Lower total cost of ownership (TCO)

The Symbol SE950/SE955 enables the development of products that offer superior manageability. Built-in system performance monitoring enables remote access to scan engine statistics. Management of your products is easier, less time consuming and less expensive — a competitive advantage for you and a lower TCO for your customers.

Rapid and flexible integration

The miniature Symbol SE950/SE955 is designed to easily integrate into the products you design today — and tomorrow. The industry standard form factor allows you to easily upgrade your current scan engine without the expense of changing your tooling processes, allowing you to offer the latest technology without the time and cost associated with changing your production line. For more information on the Symbol SE950/SE955, access our global contact directory at www.symbol.com/contact or visit us on the web at www.symbol.com/se950955

SPECIFICATION SHEET

SYMBOL SE950/SE955
OEM scan engine

Programmable scan angle

Provides flexibility to easily and cost-effectively customize products for specific applications

RoHS compliant

Meets RoHS requirements

Die cast zinc chassis and single board construction

Shock rating of 2,000G for outstanding durability

Liquid Polymer scan element

Eliminates friction and wear for superior durability and reliability

Flash upgradeable

Easy to upgrade software

Symbol SE950/SE955 Specifications

SYMBOL SE950 SCAN ENGINE SPECIFICATIONS (UNDECODED)

Physical Characteristics

Dimensions:	.46H x .85W x .61D (in) 11.55H x 21.6W x 15.5D (mm)
Weight:	.27 oz./ 7.5 g
Configuration:	undecoded
Interface:	DPB and I ² C control on a 10 pin ZIF connector

User Environment

Ambient Light	Artificial: 450 ft. candles (4,844 Lux) Sunlight: 10,000 ft. candles (107,640 Lux)
Operating Temp.:	-4° to 140°F (-20° to 60°C)
Storage Temp.:	-40° to 158°F (-40° to 70°C)
Humidity:	5% to 95% non-condensing
Power:	Input Voltage: 3.3 VDC± 10% Scan Current: 76 mA typical Standby Current: 12 µA max.
Shock Rating:	2,000 G

Regulatory

Laser Classification:	Intended for use in CDRH Class II and IEC Class 2 devices - Optional Class I model
Electrical Safety:	UL 60950, EN/IEC 60950
Environmental:	RoHS compliant
EMI/RFI:	FCC Part 15 Class B, EN 55024/CISPR 22, AS 3548, VCCI

Performance Characteristics

Light Source:	Visible Laser Diode 650 nm
Scan Rate:	104 (±) 12 scans/sec (bi-directional)
Scan Angle:	47° ± 3° (typical) / 35° ± 3° (narrow)
Scan Patterns:	Linear
Minimum Print Contrast:	Minimum 20% absolute dark/light reflectance measured at 650 nm
Ranges - 1D codes:	4 mil: Code 39; 2.5:1 - 80% MRD: 1 - 5.5 (in) / 2.5 - 13.97 (cm) 5 mil: Code 39; 2.5:1 - 80% MRD: 1.25 - 8 (in) / 3.18 - 20.32 (cm) 7.5 mil: Code 39; 2.5:1 - 80% MRD: 1.5 - 13 (in) / 3.81 - 33.02 (cm) 10 mil: Code 39; 2.5:1 - 90% MRD: 1.5 - 18 (in) / 3.81 - 45.72 (cm) 13 mil: 100% UPC - 90% MRD: 1.5 - 24 (in) / 3.81 - 60.96 (cm) 15 mil: Code 39; 2.5:1 - 80% MRD: 1.5 - 28 (in) / 3.81 - 71.12 (cm) 20 mil: Code 39; 2.2:1 - 80% MRD: 1.75 - 33 (in) / 4.45 - 83.82 (cm) 40 mil: Code 39; 2.2:1 - 80% MRD: * - 36 (in) / x - 91.44 (cm) (dependent on width of barcode) 55 mil: Code 39; 2.2:1 - 80% MRD: * - 45 (in) / x - 114.30 (cm) (dependent on width of barcode)

(* = dependent on width of bar code)

SYMBOL SE955 SCAN ENGINE SPECIFICATIONS (DECODED)

Physical Characteristics

Dimensions:	SE-955-1100R (3.3V): .46H x .85W x .61D (in) / 11.8H x 21.6W x 15.5D (mm) SE-955-1105R (5V): .48H x .85W x .89D (in) / 12.1H x 21.6W x 22.6D (mm)
Weight:	.28 oz./ 8 g
Configuration:	decoded
Interface:	SSI Control over TTL Serial on a 12 pin ZIF connector

User Environment

Ambient Light	Artificial: 450 ft. candles (4,844 Lux) Sunlight: 10,000 ft. candles (107,640 Lux)
Operating Temp.:	-4° to 140°F (-20° to 60°C)
Storage Temp.:	-40° to 158°F (-40° to 70°C)
Humidity:	5% to 95% non-condensing
Power:	Input Voltage: SE-955-1100R (3.3V): 3.3 ± 10% SE-955-1105R (5V): 5V ± 10% Scan Current: SE-955-1100R (3.3V): 86mA SE-955-1105R (5V): 90mA Standby Current: SE-955-1100R (3.3V): 12µA SE-955-1105R (5V): .35µA
Shock Rating:	2,000 G

Regulatory

Laser Classification:	Intended for use in CDRH Class II and IEC Class 2 devices - Optional Class I model
Electrical Safety:	UL 60950, EN/IEC 60950
Environmental:	RoHS compliant
EMI/RFI:	FCC Part 15 Class B, EN 55024/CISPR 22, AS 3548, VCCI

Performance Characteristics

Light Source:	Visible Laser Diode 650 nm
Scan Rate:	104 (±) 12 scans/sec (bi-directional)
Scan Angle:	47° ± 3° (typical) / 35° ± 3° (narrow)
Scan Patterns:	Linear
Minimum Print Contrast:	Minimum 20% absolute dark/light reflectance measured at 650 nm
Symbologies Supported:	All major 1D bar codes
Programmable Parameters:	Laser On Time, Aim Duration, Power Mode, Trigger Mode, Bi-directional Redundancy, Symbology Types/Lengths, Data Formatting, Serial Parameters, Beeper Tone, Scan Angle
Ranges - 1D codes:	4 mil: Code 39; 2.5:1 - 80% MRD: 1 - 5.5 (in) / 2.5 - 13.97 (cm) 5 mil: Code 39; 2.5:1 - 80% MRD: 1.25 - 8 (in) / 3.18 - 20.32 (cm) 7.5 mil: Code 39; 2.5:1 - 80% MRD: 1.5 - 13 (in) / 3.81 - 33.02 (cm) 10 mil: Code 39; 2.5:1 - 90% MRD: 1.5 - 18 (in) / 3.81 - 45.72 (cm) 13 mil: 100% UPC - 90% MRD: 1.5 - 24 (in) / 3.81 - 60.96 (cm) 15 mil: Code 39; 2.5:1 - 80% MRD: 1.5 - 28 (in) / 3.81 - 71.12 (cm) 20 mil: Code 39; 2.2:1 - 80% MRD: 1.75 - 33 (in) / 4.45 - 83.82 (cm) 40 mil: Code 39; 2.2:1 - 80% MRD: * - 36 (in) / x - 91.44 (cm) (dependent on width of barcode) 55 mil: Code 39; 2.2:1 - 80% MRD: * - 45 (in) / x - 114.30 (cm) (dependent on width of barcode)

(* = dependent on width of bar code)



MOTOROLA

motorola.com