



AT880

Library, Logistics, Military, Warehouse, Hospital etc.

Series Highlights:

- Windows CE 5.0 / Windows Embedded handheld 6.5
- Marvell™ PXA 320 806Mhz
- Memory 256MB (512MB Option) RAM / 512MB (1GB Option) ROM
- RFID UHF 900MHz GEN2, ISO/IEC 18000-6C / 18000-6B (Option)
- HF 13.56MHz ISO15693, MIFARE, ISO14443 A/B (Option)
- 1D Laser or 2D Imager Barcode Scanner (2D Long Range Barcode*)
- WLAN IEEE802.11 b/g/a (a/b/g/n, option)
- Bluetooth Class II, v2.1 + EDR
- Camera with Flash I GPS

Atid Co., Ltd.

Byuksan/GyungIn Digital Valley-II #1210, 184 Gasan Digital 2-Ro, Gumcheon-Gu, Seoul, KOREA, #153-783
Tel : +82-2-544-1436 Fax : +82-2-2113-0040 E-mail : atid@atid1.com www.atid1.com

AT880

Library, Logistics, Military, Warehouse, Hospital etc.



FRONT



BACK



SIDE



UHF GUN READER

ACCESSORIES



Adaptor AC Cable

Protection Film

Handstrap

Cradle

GUN Handle

USB Cable

SPECIFICATION

Performance Characteristics

Processor	Marvell™ PXA 320 806MHz
Operating System	Windows CE 5.0 / Windows Embedded handheld 6.5
Memory	256MB (512MB*) RAM / 512MB (1GB*) ROM
Display	3.5" QVGA with Backlight, TFT LCD, 240x320 Pixel, 262, 144 Color (VGA*)
Weight	280g (PDA only, without battery)
Operating Temp.	-20 °C ~ 60 °C
Storage Temp.	-30 °C ~ 70 °C
Humidity	95% non-condensing
Drop Spec.	1.5M Drop to concrete
Dust & Water Proof	IP65

Physical Characteristics

Audio	Phone Receiver, Speaker, Ear Jack, Microphone
Standard I/O Port	USB 1.1 Client / USB Host & Serial (RS-232) via gender cable or Cradle
Expansion Slot	1Micro SD Slot (SDHC), 1SIM Slot, 1SAM Slot
Notification	Vibrator and LED, Speaker
Dimensions(L x W x H)	159 x 79 x 27 (35.2)mm

Battery Supply

Main Battery	Lithium-Ion Polymer 3.7V 2,960mAh (Rechargeable) Up to 4,400mAh*
Backup Battery	Lithium-Ion Polymer 3.7V 80mAh (Rechargeable)
Power Adapter	Input AC110V ~ 240V / Output DC 5V 3A

Network Characteristics

WLAN	IEEE 802.11 b/g/a (a/b/g/n*) Compliant
Bluetooth	Class II, v2.1 + EDR
Radio	MODEM 3G (GSM / GPRS / HSDPA / HSPA+)
GPS	Internal Antenna

Data Capture Device

Barcode Engine	1D Laser or 2D Imager Barcode Scanner (2D Long Range Barcode*)
Camera	3.0 Mega Pixel Auto Focus with Flash

UHF 900 Mhz Reader/Writer

Frequency	860MHz~960MHz
Reading range	0M ~ 7M (According to Tag & Environment)
Writing range	0M ~ 3M (According to Tag & Environment)
RF output	1W EIRP
Protocol	GEN2, ISO/IEC 18000-6C, 18000-6B*
Special function	Anti-Collision

HF 13.56Mhz Reader/Writer

Applied RFID Tag	ISO15693, MIFARE, ISO14443 A/B*
Reading range	Based On Tag : 0 ~ 10Cm (Internal or External)

Cradle

Standard Interface	USB 1.1 Host / USB Client / DC Power Jack / Extra Battery Charger / Serial (RS232) via gender cable
Ethernet Interface	RJ-45 Ethernet Interface*

Accessories*

Gun Handle Grip (Pistol Grip)	Body, UHF /HF Available
Gun Handle Battery	Lithium-Ion 3.7V 4,400mAh (Rechargeable)*



* All Features and specifications described are subject to change without notice.